

LED Mini Globe



Features & Benefits

- Ideal replacement for high power consumption incandescent globe
- No flicker, mercury or UV emission associated with health hazards
- Opal diffuser for reduced glare
- No warm up time, meaning instant full brightness when switched on
- Incredible longevity up to 15,000 hours of practical lifespan, meaning frequent globe replacement is not required, hence very low maintenance cost
- Very good colour rendering ability, ensuring elegant reproduction of object colours

Options

- Available in small ES and BC base
- Available in mellow tone (warm white colour appearance)




Ordering Information

Part No.	Barcode	Power	Colour	CCT	Flux	Cap	Length	Width	Alternative to
RG45006T0101	6922619685765	5.5W	Warm white	2700K	470lm	E14	93mm	45mm	40W GLS
RG45006T0102	6922619685772	5.5W	Warm white	2700K	470lm	B22	91mm	45mm	40W GLS


Specifications

- Power consumptions: 5.5W
- Input voltage: 220-240V~
- Dimmable: No
- Luminous flux: 470lm
- Colour appearance: warm white
- Colour temperature: 2700K
- Colour rendering index (Ra): 80+
- Beam angle: 190°
- Lumen maintenance (L70 B50): 15,000 hours
- Cap fitting (base): E14 or B22
- Operating temperature: -20°C to +45°C
- Switch times: 20,000
- Carton quantity: 12 pcs

Dimensions



Photometry



5.5W

ReneSola Partner

Telephone



ReneSola's Global Office Network

Follow us



Melbourne: 18 Corporate Blvd Bayswater, VIC 3153
Brisbane: 2/103 Buchanan Road, Banyo, QLD 4014
ABN: 58 159 368 859 | ACN: 159 368 859

All rights reserved. Specifications are subject to change without prior notice.