

CROSSFIRE

E5

E5

13.5 HP ELECTRIC AC MOTOR | SELECTABLE DRIVE POWER MODES
INDEPENDENT FRONT AND REAR SUSPENSION | METAL TRAY
LOCKABLE REAR DIFFERENTIAL | HALF CABIN DOORS
WINDSCREEN | TOW HITCH



 **CROSSFIRE**

CROSSFIRE E5



13.5 Hp Electric ATV

IMAGES



DESCRIPTION

The new level of affordability meets technology.

Quiet and clean traffic, zero emissions and long range. These are the key benefits that give Crossfire E-5 UTV a wide range of uses – from maintenance of golf courses, parks and urban greenery through work in zoological and botanical gardens to unrestricted access to warehouses, factory halls, industrial premises and enclosed spaces. The Rear wheel drive E5 has a lockable rear differential for when maximum traction is required while you can unlock the rear differential (Turf Mode) for maximum maneuverability and being gentle on your lawns.

100% Electric
100% Torque off the line
100% No emissions during use
100% Quiet

The Crossfire E-5 can handle everything that works hard. And there is no noise, no exhaust gases, and it is much less costly than UTV with the engine.

The Crossfire E-5 will surprise you with a low operating cost: it does not need gasoline, diesel or gas, no engine oil and filter changes, and it is as robust as any other UTV. The easy-to-use chassis ensures a safe and stable ride, the large tilting body can easily be converted into a spacious platform.

And then there's the equipment: the Crossfire E5 features a full frontal windscreen, plastic roof, massive front frame, side door, head restraints and attractive cast aluminium wheels.

SPECIFICATIONS

Motor Type	Three phase induction electric motor with copper rotor
Battery Voltage Performance	60V 9.7 kW / 1950-2100 rpm
Battery Type	5x maintenance-free battery Varta Professional Deep Cycle AGM 12V / 150Ah
Charge Time	8-9 am
Range: ECONOMY mode:	90 km *
Range: POWER mode:	85 km *
* Data on the roll based on the driving average speed of 30 km / h without load.	
Drivetrain	
Drive	2x4 – Rear
Speed	Forward, neutral, reverse Electronic / 2 driving modes – POWER and ECONOMY
Final Drive Ratio	Direct drive rear half
Chassis / Suspension / Brakes	
Suspension Front	Independent McPherson Hydraulic fluid dampers
Suspension Rear	Independent, double A-arm IRS hydraulic liquid dampers, p RUŽÍN with adjustable preload
Brakes Front & Rear	2x hydraulic disc with drilled discs
Tyres	Front: AT 24 x 8-12 Rear: AT 24 x 8-12
Dimensions	
Length x Width x Height	2700 mm x 1420 mm x 1870 mm
Wheelbase	1805 mm
Seat Height	850 mm
Cargo Bed Dimensions	1100 x 930 x 235 mm
Operating Weight	442 kg
Total Payload	534 kg (driver + passenger + cargo in the back)
Other	
Display	Digital multifunction display features: Speedometer Odometer Mileage counter reading Board clocks
Lights	Direction indicators, main beam LED headlights, LED tail / brake lights
Warranty	2-Year Manufacturer Warranty

AVAILABLE IN:

