



Guardian

EMERGENCY EYEWASH AND SHOWER TECHNOLOGY

WA SAFETY
Helping You Work Safely



We are proud to present the Guardian range of Emergency Shower and Eyewash Equipment. A premium range of products that has been manufactured in the US for 30 years, and shipped all over the globe.

Guardian equipment carries out all manufacturing activities under their own roof, ensuring peace of mind with strict QA standards, and testing of all products before they leave the factory.

Performance: Guardian emergency equipment utilizes the exclusive GS-Plus and FS-Plus spray type outlet heads. Water is delivered to the user's eyes and face in a soft, aerated, wide spray, rather than a narrow solid stream. In an emergency, contaminants are rinsed away quickly, gently, and completely.

Durability: Guardian products are engineered and built to withstand the harshest industrial conditions. Materials are carefully selected for strength and corrosion resistance. Every valve in every unit we sell is made in the US. Because of this, we are able to back all of our products with a full 2 year warranty.

Read on to view our range, and if your requirement is not listed, please ask as we will be able to customize to exactly what you need.

Eye Wash, Wall Mounted, Plastic Bowl



Product # **AM-G1814P**

Application: Eyewash for wall mounting. Two GS-Plus™ spray-type heads deliver a flood of water for rinsing eyes.

Spray Head Assembly: Two GS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Mounting: Heavy duty cast aluminum wall bracket with corrosion resistant powder coated finish.

Quality Assurance: Unit is completely assembled and water tested prior to shipment .

Eye Wash, Wall Mounted, Stainless Steel Bowl



Product # **AM-G1814**

Application: Eyewash for wall mounting. Two GS-Plus™ spray-type heads deliver a flood of water for rinsing eyes.

Spray Head Assembly: Two GS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Mounting: Heavy duty cast aluminum wall bracket with corrosion resistant powder coated finish.

Quality Assurance: Unit is completely assembled and water tested prior to shipment .

Eye Wash, Wall Mounted, No Bowl



Product # **AM-G1819**

Application: Eyewash for wall mounting . Two GS-Plus™ spray-type heads deliver a flood of water for rinsing eyes. Unit is provided without bowl or drain for waste water. Note: Floor drain should be provided underneath unit to prevent accumulation of water on floor.

Spray Head Assembly: Two GS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Mounting: Heavy y duty aluminum wall bracket with corrosion resistant powder coated finish.

Construction: Polished chrome plated brass.

Quality Assurance: Unit is completely assembled and water tested prior to shipment .

Eye Wash, Wall Mounted, Stainless Steel Bowl and Cover



Product # **AM-G1814BC**

Application: Free standing , pedestal mounted eyewash. Two GS-Plus™ spray-type heads deliver a flood of water for rinsing eyes.

Spray Head Assembly: Two GS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Quality Assurance: Valve, bowl and spray head assembly is factory assembled and water tested prior to shipment .

Eye Wash, Pedestal Mounted, Stainless Steel Bowl



Product # AM-G1825

Application: Free standing, pedestal mounted eyewash. Two GS-Plus™ spray-type heads deliver a flood of water for rinsing eyes.

Spray Head Assembly: Two GS-Plus™ spray heads. Each head has a "flip top" dust cover, internal flow control and filter to remove impurities from the water flow.

Quality Assurance: Valve, bowl and spray head assembly is factory assembled and water tested prior to shipment.

Eye Wash, Pedestal Mounted, Stainless Steel Bowl and Cover



Product # AM-G1825BC

Application: Free standing, pedestal mounted eyewash. Unit has stainless steel cover to protect bowl from dust, dirt and other contaminants. Two GS-Plus™ spray-type heads deliver a flood of water for rinsing eyes.

Spray Head Assembly: Two GS-Plus™ spray heads. Each head has an internal flow control and filter to remove impurities from the water flow.

Bowl: Stainless steel with bowl cover. Cover is raised automatically when flag handle is activated. Cover closes when handle is returned to closed position.

Quality Assurance: Valve, bowl and spray head assembly is factory assembled and water tested prior to shipment.

**Eye/Face Wash, Wall Mounted,
 Plastic Bowl**



Product # AM-G1750P

Application: Eye / Face wash for wall mounting . Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face .

Spray Head Assembly: Two FS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Mounting: Heavy duty cast aluminum wall bracket with corrosion resistant powder coated finish.

Quality Assurance: Unit is completely assembled and water tested prior to shipment .

**Eye/Face Wash, Wall Mounted,
 Stainless Steel Bowl**



Product # AM-G1750

Application: Eye / Face wash for wall mounting . Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face .

Spray Head Assembly: Two FS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Mounting: Heavy duty cast aluminum wall bracket with corrosion resistant powder coated finish.

Quality Assurance: Unit is completely assembled and water tested prior to shipment .

**Eye/Face Wash, Wall Mounted,
 No Bowl**



Product # AM-G1771

Application: Eye /face wash for wall mounting . Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face . Unit is provided without bowl or drain for waste water. Note: Floor drain should be provided underneath unit to prevent accumulation of water on floor.

Spray Head Assembly: Two FS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Mounting: Heavy duty aluminum wall bracket with corrosion resistant powder coated finish.

Construction: Polished chrome plated brass.

Quality Assurance: Unit is completely assembled and water tested prior to shipment .

**Eye/Face Wash, Wall Mounted,
 Stainless Steel Bowl and Cover**



Product # AM-G1750BC

Application: Eye /face wash for wall mounting . Unit has stainless steel cover to protect bowl from dust, dirt and other contaminants. Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face .

Spray Head Assembly: Two FS-Plus™ spray heads. Each head has an internal flow control and filter to remove impurities from the water flow.

Bowl: Stainless steel bowl with cover. Cover is raised automatically when flag handle is activated. Cover closes when handle is returned to closed position.

Mounting: Heavy duty cast aluminum wall bracket with powder coated finish.

Quality Assurance: Unit is completely assembled and water tested prior to shipment .

Eye/Face Washes

Eye/Face Wash, Pedestal Mounted, Stainless Steel Bowl



Product # AM-G1760

Application: Free standing, pedestal mounted eye /face wash. Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face.

Spray Head Assembly: Two FS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Quality Assurance: Valve, bowl and spray head assembly is factory assembled and water tested prior to shipment.

Eye/Face Wash, Pedestal Mounted, Stainless Steel Bowl, Hand and Foot Control



Product # AM-G1760HFC

Application: Free standing, pedestal mounted eye /face wash. Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face. Water flow is activated by either flag handle or foot treadle.

Spray Head Assembly: Two FS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Quality Assurance: Valve, bowl and spray head assembly is factory assembled and water tested prior to shipment.

Eye/Face Wash, Pedestal Mounted, Stainless Steel Bowl & Cover



Product # AM-G1760BC

Application: Free standing , pedestal mounted eye /face wash. Unit has stainless steel cover to protect bowl from dust, dirt, and other contaminants. Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face .

Spray Head Assembly: Two FS-Plus™ spray heads. Each head has a "flip top" dust cover, internal flow control and filter to remove impurities from the water flow.

Bowl: Stainless steel bowl with cover. Cover is raised automatically when flag handle is activated. Cover closes when handle is returned to closed position.

Quality Assurance: Valve, bowl and spray head assembly is factory assembled and water tested prior to shipment.

Eye/Face Wash, Pedestal Mounted, Stainless Steel Bowl & Cover, Hand and Foot Control



Product # AM-G1760BC-HFC

Application: Free standing , pedestal mounted eye /face wash. Unit has stainless steel cover to protect bowl from dust, dirt, and other contaminants. Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face . Water flow is activated by either flag handle or foot treadle .

Spray Head Assembly: Two FS-Plus™ spray heads. Each head has a "flip top" dust cover, internal flow control and filter to remove impurities from the water flow.

Bowl: Stainless steel bowl with cover. Cover is raised automatically when flag handle is activated. Cover closes when handle is returned to closed position.

Quality Assurance: Valve, bowl and spray head assembly is factory assembled and water tested prior to shipment.

Emergency Showers

Emergency Shower, Vertically Mounted, Plastic Shower Head



Product # AM-G1635

Application: Emergency shower for vertical mounting.

Emergency Shower, Free Standing, Plastic Shower Head



Emergency Shower, Horizontal Mounted, Plastic Shower Head



Product # AM-G1643

Application: Emergency shower for horizontal mounting.

Product # AM-G1662

Application: Free standing emergency shower.

**Emergency Shower, Eye Wash,
 Stainless Steel Bowl**



Product # AM-G1902

Application: Combination eyewash and shower safety station. Two GS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes.

Spray Head Assembly: Two GS-Plus™ spray heads. Each head has a "flip top" dust cover, internal flow control and filter to remove impurities from water.

Quality Assurance: Valve and spray head assemblies are factory assembled and water tested prior to shipment.

**Emergency Shower, Eye Wash,
 Stainless Steel Bowl & Cover**



Product # AM-G1902BC

Application: Combination eyewash and shower safety station. Eyewash has stainless steel cover to protect bowl from dust, dirt and other contaminants. Cover is raised automatically when flag handle is activated. Cover closes when handle is returned to closed position. Two GS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes.

Spray Head Assembly: Two GS-Plus™ spray heads. Each head has an internal flow control and filter to remove impurities from water.

Quality Assurance: Valve and spray head assemblies are factory assembled and water tested prior to shipment.

Emergency Showers

Modesty Curtain for Emergency Shower



Product # AM-AP250-015

Application: In an emergency, it is imperative that contaminated clothing be removed as quickly as possible. However, employees may be reluctant to remove their clothing in the presence of co-workers. A modesty curtain will protect the privacy of the user and permit disrobing while the shower unit is in operation. The curtain has a pocket in which a smock can be stored.

Installation: Unit is designed for use with horizontally mounted emergency showers and free-standing combination safety stations. Furnished complete with stainless steel track assembly for mounting on vertical and horizontal piping. All necessary mounting brackets and clamps are included.

Curtain: White UV-resistant nylon curtain with ring hangers. Curtain has tie-back so it can be neatly stored when shower is not in use. Curtain has interior pocket for storing a smock to be used after contaminated clothing is removed.

Emergency Shower, Eye/Face Wash, No Bowl



Product # AM-G1931

Application: Combination eye/face wash and shower safety station. Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face. Unit is provided without bowl or drain for waste water. **Note:** Floor drain should be provided underneath unit to prevent accumulation of water on floor.

Spray Head Assembly: Two FS-Plus™ spray heads. Each head has a "flip top" dust cover, internal flow control and filter to remove impurities from water.

Quality Assurance: Valve and spray head assemblies are factory assembled and water tested prior to shipment.

Emergency Shower, Eye/Face Wash, Stainless Steel Bowl



Emergency Shower, Eye/Face Wash, Stainless Steel Bowl & Cover



Product # AM-G1950

Application: Combination eye/face wash and shower safety station. Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face.
 Spray Head Assembly: Two FS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from water.
 Quality Assurance: Valve and spray head assemblies are factory assembled and water tested prior to shipment.

Product # AM-G1950BC

Application: Combination eye/face wash and shower safety station. Eye/face wash has stainless steel cover to protect bowl from dust, dirt and other contaminants. Cover is raised automatically when flag handle is activated. Cover closes when handle is returned to closed position. Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face.
 Spray Head Assembly: Two FS-Plus™ spray heads. Each head has an internal flow control and filter to remove impurities from water.
 Quality Assurance: Valve and spray head assemblies are factory assembled and water tested prior to shipment.

Emergency Showers

Emergency Shower, Eye/Face Wash, Stainless Steel Bowl, Hand & Foot Control



Product # AM-G1950HFC

Application: Combination eye/face wash and shower safety station. Eye/face wash is activated by flag handle or foot treadle. Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face.

Spray Head Assembly: Two FS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

Quality Assurance: Valve and spray head assemblies are factory assembled and water tested prior to shipment.

Emergency Shower, Eye/Face Wash, Stainless Steel Bowl & Cover, Hand & Foot Control



Product # AM-G1950BC-HFC

Application: Combination eye/face wash and shower safety station. Eye/face wash has stainless steel cover to protect bowl from dust, dirt and other contaminants. Cover is raised automatically when flag handle is activated. Cover closes when handle is returned to closed position. Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face.

Spray Head Assembly: Two FS-Plus™ spray heads. Each head has an internal flow control and filter to remove impurities from water.

Quality Assurance: Valve and spray head assemblies are factory assembled and water tested prior to shipment.

Eye Wash/Drench Hose Unit, Deck Mounted



Eye Wash/Drench Hose Unit, Wall Mounted



Product # AM-G5022

Application: Dual purpose eye wash/drench hose for deck mounting. Unit meets the provisions of ANSI Z358.1 - 2009 as both an eye wash and a drench hose. Unit may be left in the deck flange for use as a fixed eye wash, leaving user's hands free. Alternatively, unit may be removed for use as a drench hose to rinse any part of user's eyes, face or body.

Spray Head Assembly: Two GS-Plus™ spray heads mounted side-by-side. Each head has a "flip top" dust cover, internal flow control and filter to remove impurities from the water flow.

Hose: 8' reinforced PVC hose. 300 PSI maximum working pressure.

Mounting: Deck flange for countertop mounting. Flange has handle locator guide to position spray heads and handle facing forward at all times.

Quality Assurance: Unit is completely assembled and water tested prior to shipment.

Product # AM-G5026

Application: Dual purpose eyewash/drench hose for wall mounting. Unit meets the provisions of ANSI Z358.1 - 2009 as both an eyewash and a drench hose. Unit may be left in the mounting bracket for use as a fixed eyewash, leaving user's hands free. Alternatively, unit may be removed for use as a drench hose to rinse any part of user's eyes, face or body.

Spray Head Assembly: Two GS-Plus™ spray heads mounted side-by-side. Each head has a "flip top" dust cover, internal flow control and filter to remove impurities from the water flow.

Hose: 8' reinforced PVC hose. 300 PSI maximum working pressure.

Mounting: Bracket with spring clips to hold unit on wall. Clips position spray heads and handle to face forward at all times.

Quality Assurance: Unit is completely assembled and water tested prior to shipment.

Eye Wash/Drench Hose Unit, Wall Mounted, 12 inch Hose



Product # AM-G5046

Application: Dual purpose eyewash/drench hose for wall mounting. Unit meets the provisions of ANSI Z358.1 - 2009 as both an eyewash and a drench hose. Unit may be left in the mounting bracket for use as a fixed eyewash, leaving user's hands free. Alternatively, unit may be removed for use as a drench hose to rinse any part of user's eyes, face or body.

Spray Head Assembly: Two GS-Plus™ spray heads mounted side-by-side. Each head has a "flip top" dust cover, internal flow control and filter to remove impurities from the water flow.

Hose: 12' reinforced nylon retractable coiled hose.

180 PSI maximum rated working pressure.

Mounting: Bracket with spring clips to hold unit on wall. Clips position spray heads and handle to face forward at all times.

Quality Assurance: Unit is completely assembled and water tested prior to shipment.

Drench Hose Units, Deck Mounted



Product # AM-G5025

Application: Drench hose unit for wall mounting. Ideal for rinsing any part of user's eye, face or body. Note: Under ANSI Z358.1 - 2009, drench hose units supplement, but do not replace, other types of emergency equipment.

Spray Head: Single FS-Plus™ spray head. Spray head has "flip top" dust cover, internal flow control and filter to remove impurities from the water flow.

Hose: 8' reinforced PVC hose. 300 PSI maximum working pressure.

Mounting: Wall mounted hook holds unit on wall.

Quality Assurance: Unit is completely assembled and water tested prior to shipment.

Drench Hose Units, Wall Mounted



Product # AM-G5020

Application: Drench hose unit for deck mounting. Ideal for rinsing any part of user's eye, face or body. Note: Under ANSI Z358.1 - 2009, drench hose units supplement, but do not replace, other types of emergency equipment.

Spray Head: Single FS-Plus™ spray head. Spray head has "flip top" dust cover, internal flow control and filter to remove impurities from the water flow.

Hose: 8' reinforced PVC hose. 300 PSI maximum working pressure.

Mounting: Deck flange for countertop mounting. Flange has handle locator guide to position handle to face forward at all times.

Quality Assurance: Unit is completely assembled and water tested prior to shipment.

Emergency Showers Accessories

Anti-Scald Valve



Can be ordered at time of purchase. Not a retrofit unit.

Electric Alarm Unit With Light & Horn



Product # AM-AP275-100

Application: Alarm units serve two important functions when installed in conjunction with emergency eyewash and shower equipment. First, alarms serve to alert facility personnel that an accident has occurred and that assistance to the user may be required. Second, alarms deter unintended or malicious operation of the emergency equipment. For this reason, they are advisable in schools and other areas where the possibility of vandalism is present. Alarms are activated by a flow switch that senses the movement of water in the supply line when the safety unit is activated. Once activated, the bright light turns on and the horn sounds loudly.

Visual Signal: Weatherproof amber beacon light with shatter-resistant lens and protective metal grid.

Audible Signal: Weatherproof horn delivers distinctive, urgent signal. Volume is preset at 100 db at 10 feet.

An adjustment screw on the front of horn allows adjustment of output sound level.

Mounting: Furnished complete with bracket for mounting on vertical pipe or wall, junction box and 5 foot flexible, NEMA 4X cord and receptacle. Electrical connection by others.

Quality Assurance: Unit is fully assembled, wired and factory tested prior to shipment.

Test Chute with Extension Rod and Bucket



Product # AP250-005

Description: Test Chute with Extension Rod and 5 Gallon Bucket

Aquaguard Gravity-Flow Portable Eye Wash, 16 Gallon



Product # AM-G1540

Application: Self-contained 16 gallon gravity flow eyewash unit uses gravity to deliver water through dual spray heads. Unit delivers over eight gallons (30 liters) of water for fifteen minutes, thus complying with the provisions of ANSI Z358.1-2009 for eyewashes. Unit has a rugged plastic tank that can be installed in a wide variety of locations. Unit is ideal for use where a continuous supply of potable water is not available, especially in remote plant areas, low traffic and/or low hazard areas.

Tank: 16 gallon capacity safety green Poly tank. Tank has built-in carrying handle, heavy wall construction and reinforced ribs to support weight of unit.

Spray Head Assembly: Water flow is activated by pulling down on bright yellow eye wash tray. Integral full flow nozzles deliver soft spray of water. Swing tray up to storage position to stop flow.

Mounting: Furnished with epoxy coated steel bracket for mounting unit on wall. Unit can also be placed on countertop or other flat surface.

Preparation: Top operate unit, fill unit with clean potable water and add bacteriostatic additive. Additive protects against growth of bacteria, fungus, algae and acanthamoeba. Unit should be inspected regularly and water in unit should be changed at least once every six months.

Discharge time: Eyewash delivers over .5 gallons per minute for 15 minutes.

Quality Assurance: Unit is completely assembled and water tested prior to shipment.

15 Gallon Portable Eye Wash/ Drench Hose Unit



Product # AM-G1562

Application: Self-contained eyewash and/or drench hose units are ideal where a continuous supply of potable water is not available. These units may be used in low traffic areas, low hazard areas or where installation of plumbed equipment is not cost effective. Fifteen gallon units provide approximately 10 usable gallons (37.9 liters) of water for effective rinsing of the eyes, face or body. Note that, under ANSI Z358.1-2009, drench hose units supplement but do not replace other types of emergency equipment.

Tank: 15 gallon stainless steel pressurized tank. Tank has built-in carrying handles, air intake fitting, pressure gauge and pressure relief valve. Tank has approximately 10 gallons (37.9 liters) usable capacity.

Eyewash unit: Two GS-Plus spray heads, each with a "flip top" dust cover, internal flow control and filter. 1/2" IPS chrome plated brass stay-open ball valve with flag handle. Pressure regulator controls eyewash flow to 0.65 GPM for 15 minutes.

drench hose: Single GS-Plus spray head with "flip top" dust cover, internal flow control and filter. Chrome plated brass squeeze valve with stainless steel lever handle and 6 ft. reinforced PVC hose.

Operation: To operate unit, fill with clean potable water and add bacteriostatic additive (supplied with unit). Additive protects against growth of bacteria, fungus, algae and acanthamoeba inside unit. After filling with water, pressurize unit to 80 PSI air pressure. If necessary, adjust pressure regulator to achieve maximum flow for fifteen minutes. Unit should be inspected regularly and water in unit should be changed at least once every six months. Filling instructions included.

Weight: 35.6 lbs. empty, 118.9 lbs. filled.

Quality assurance: Unit is fully assembled, pressurized and water tested at the factory. Unit is depressurized and emptied prior to shipping. Some assembly required in field.

Bacteriostatic Additive for Portable Units

Product # AM-G1540BA-R

Application: Self-contained eyewash and/or drench hose units are ideal where a continuous supply of potable water is not available. These units may be used in low traffic areas, low hazard areas or where installation of plumbed equipment is not cost effective. Fifteen gallon units provide approximately 10 usable gallons (37.9 liters) of water for effective rinsing of the eyes, face or body. Note that, under ANSI Z358.1-2009, drench hose units supplement but do not replace other types of emergency equipment.

Tank: 15 gallon stainless steel pressurized tank. Tank has built-in carrying handles, air intake fitting, pressure gauge and pressure relief valve. Tank has approximately 10 gallons (37.9 liters) usable capacity.

Eyewash unit: Two GS-Plus spray heads, each with a "flip top" dust cover, internal flow control and filter. 1/2" IPS chrome plated brass stay-open ball valve with flag handle. Pressure regulator controls eyewash flow to 0.65 GPM for 15 minutes.

Drench hose: Single GS-Plus spray head with "flip top" dust cover, internal flow control and filter. Chrome plated brass squeeze valve with stainless steel lever handle and 6 ft. reinforced PVC hose.

Operation: To operate unit, fill with clean potable water and add bacteriostatic additive (supplied with unit). Additive protects against growth of bacteria, fungus, algae and acanthamoeba inside unit. After filling with water, pressurize unit to 80 PSI air pressure. If necessary, adjust pressure regulator to achieve maximum flow for fifteen minutes. Unit should be inspected regularly and water in unit should be changed at least once every six months. Filling instructions included.

Quality Assurance: Unit is completely assembled, pressurized and water tested prior to shipment.



Full range of parts for complete backup and life cycle servicing. All parts are genuine US manufactured Gardien branded.